

## LED Tube



A new LED tube for retrofit general lighting application, this tube demonstrates direct energy savings, as well as indirect cost savings realized from a reduction in maintenance cost. Using famous high quality, high flux 5mm LEDs, with intelligent self-thermal detect and protect functions; this tube is a safe, easy solution to retrofit fluorescent tube .

### **Special Features:**

- Low power consumption
- Long lifetime: 40,000 hrs
- Safe, green lighting
- No UV
- No flickering
- Maintenance free, easy installation
- Universal input
- T8 size, retrofit conventional fluorescent tube. ( Remove ballast and starter)

### **Applications:**

Conference/ meeting room lighting Factory and office lighting Residential lighting



**Specifications:**

LED: Epistar 5mm high flux LED

LED Color : White / Warm white

3500K~8000K Diameter: 30mm (T10) Length: 600/1200/1500mm

Operating temperature : -20°C~45°C

**Electrical Specifications:**

Input voltage : Universal from 80V - 245V

Directly install into T10 fluorescent bracket, MUST remove ballast and starter.

**Product Model:**

<b>Model</b>	<b>GS01-T8-L60-8</b>	<b>GS01-T8-L120-15</b>	<b>GS01-T8-L120-18</b>	<b>GS01-T8-L150-18</b>
Length	600mm	1200mm	1200mm	1500mm
Power	8W	15W	18W	18W/20W
LED rated Lumen	600lm	1060lm	1500lm	1500/1800lm