

LED Lighting ② Wall Washer ② Projection Lamp



Type & Technical Parameter

Item No.	Voltage (V)	Unit Power (W)	Projection Space (M)	Function Description
DS-TG5-W	DC24	5.8	8	White continuous light
DS-TG8-W	DC24	13.5	10	
DS-TG5-R	DC15	3.6	8	Red continuous light
DS-TG8-R	DC15	8.4	10	
DS-TG5-Y	DC15	3.6	8	Yellow continuous light
DS-TG8-Y	DC15	8.4	10	
DS-TG5-B	DC24	5.8	8	Blue continuous light
DS-TG8-B	DC24	13.5	10	
DS-TG5-G	DC24	5.8	8	Green continuous light
DS-TG8-G	DC24	13.5	10	
DS-TG5-RGB	DC5	≤ 21.6	8	Changes between the various colors
DS-TG8-RGB	DC5	≤ 50.4	10	
DS-TG5-R/B	DC24	≤ 4.7	8	Changes between the three colors

DS-TG8-R/B	DC24	≤ 11	10
DS-TG8-B/G	DC24	≤ 13.5	10
DS-TG8-R/G/B	DC24	≤ 17.4	10

Changes between the various colors

Features

1. Working temperature: - 40°C to + 65°C
2. Low power Consumption
3. Breakage resistant; Dustproof, Waterproof, Protective Grade: IP 65.
4. LED usage life: 100000HRS
5. Lighting projecting angle: 10° - 60°
6. Shape: 5 inch / 8inch Ellipsoid.
7. Weight of main body: TG 5 – 0.8kg/TF8 – 1.4Kg.

Main Application

Decoration of palace and pavilion, lawn and shrub, pond and fountain, hotel, house, inside and outside of building, road, bridge, signage and hoarding, stage lighting and exhibitions, etc.